

# Especificaciones

## Eaton 9PX1000RT

Eaton 9PX UPS, 2U, 1000 VA, 900 W, 5-15P input, Outputs (8) 5-15R, 120V, Black/silver

### General specifications

|                             |                                                                              |
|-----------------------------|------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton 9PX UPS                                                                |
| <b>CATALOG NUMBER</b>       | 9PX1000RT                                                                    |
| <b>UPC</b>                  | 743172081254                                                                 |
| <b>PRODUCT LENGTH/DEPTH</b> | 17.7 in                                                                      |
| <b>PRODUCT HEIGHT</b>       | 3.4 in                                                                       |
| <b>PRODUCT WIDTH</b>        | 17.3 in                                                                      |
| <b>PRODUCT WEIGHT</b>       | 36.4 lb                                                                      |
| <b>COMPLIANCES</b>          | IEC 62040-2 Cat C1<br>CISPR22 Class B<br>FCC part 15 Class B<br>VCCI Class B |
| <b>CERTIFICATIONS</b>       | cULus Listed<br>NOM                                                          |

## Especificaciones del producto

|                             |                                                                                                                                                                                                                                                                   |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TOPOLOGY                    | Online/Double-conversion                                                                                                                                                                                                                                          |
| FORM FACTOR                 | Rack/tower                                                                                                                                                                                                                                                        |
| RACK SIZE                   | 2U                                                                                                                                                                                                                                                                |
| COLOR                       | Black/silver                                                                                                                                                                                                                                                      |
| VA RATING                   | 1000 VA                                                                                                                                                                                                                                                           |
| WATTAGE                     | 900 W                                                                                                                                                                                                                                                             |
| RACK MOUNTING KIT           | Yes                                                                                                                                                                                                                                                               |
| PACKAGE CONTENTS            | <ul style="list-style-type: none"><li>• 9PX1000RT UPS</li><li>• 4-post rail kit</li><li>• Safety manual</li><li>• User manual</li><li>• Tower pedestals</li><li>• RS-232 serial cable</li><li>• USB cable</li><li>• Intelligent Power Software Suite CD</li></ul> |
| INTERNAL BYPASS             | Yes                                                                                                                                                                                                                                                               |
| INPUT CONNECTION            | <a href="#">5-15P</a>                                                                                                                                                                                                                                             |
| INPUT NOMINAL VOLTAGE       | 120V default<br>(100/110/120/125V)                                                                                                                                                                                                                                |
| INPUT FREQUENCY RANGE       | 60 Hz: 50-70 Hz, 50 Hz: 40-60 Hz                                                                                                                                                                                                                                  |
| INPUT POWER FACTOR          | >0.99 typical                                                                                                                                                                                                                                                     |
| RECEPTACLE                  | (8) 5-15R                                                                                                                                                                                                                                                         |
| NUMBER OF OUTPUTS 5-15R     | 8                                                                                                                                                                                                                                                                 |
| OUTPUT WAVEFORM             | True sine wave                                                                                                                                                                                                                                                    |
| VOLTAGE                     | 120V                                                                                                                                                                                                                                                              |
| OUTPUT NOMINAL VOLTAGE      | 120V default<br>(100/110/120/125V)                                                                                                                                                                                                                                |
| RUNTIME GRAPH               | <code>\$row.attributeValue.cdata</code>                                                                                                                                                                                                                           |
| BATTERY MANAGEMENT          | ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)                                                                                                                                        |
| BATTERY REPLACEMENT         | Hot-swappable internal batteries and extended battery modules (EBMs)                                                                                                                                                                                              |
| BATTERY TYPE                | Sealed, lead-acid                                                                                                                                                                                                                                                 |
| EXTENDED BATTERY CAPABILITY | Add up to 4 extended battery modules (EBM).<br>Part number 9PXEBM36RT                                                                                                                                                                                             |

## Recursos

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>STANDARD FACTORY WARRANTY</b> | <ul style="list-style-type: none"> <li>• 3-YEAR FACTORY WARRANTY</li> <li>• - 3 years</li> <li>• - Parts, electronics and batteries coverage</li> <li>• - Standard ground shipping</li> <li>• - Technical support</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>EXTENDED SERVICE PLANS</b>    | <ul style="list-style-type: none"> <li>• ADVANCED DEPOT EXCHANGE</li> <li>• -5-year depot repair: 9SW5Y-1000UC</li> <li>• -Expedited parts coverage for 5 years</li> <li>• -Parts, electronics and UPS batteries coverage</li> <li>• -Next business day shipping</li> <li>• -Technical support</li> <li>•</li> <li>• 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC</li> <li>• - On-site parts and labor coverage for years 5</li> <li>• - Parts, electronics and UPS batteries coverage</li> <li>• - 24x7 on-site labor coverage, next-day response</li> <li>• - Next-day shipping</li> <li>• - Technical support</li> </ul> |
| <b>COMMUNICATION</b>             | MiniSlot expansion port + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay<br>Communication slot                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>EXPANSION SLOTS</b>           | <ul style="list-style-type: none"> <li>• (1) Mini-Slot (MS) expansion port. Optional connectivity cards</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

may be ordered separately.

- Gigabit Web/SNMP card part number: NETWORK-M3
- Modbus card part number: INDGW-M2
- Relay card part number: RELAY-MS

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| SOFTWARE COMPATIBILITY      | Intelligent Power Software Suite              |
| USER INTERFACE              | Graphical display, 5-button programmable menu |
| ALTITUDE                    | 0-1500m (0° to 40°C), 1500-3000m (0° to 35°C) |
| BTU RATING                  | Online: 330, Battery: 646                     |
| NOISE LEVEL                 | <40 dB at 1 meter                             |
| RELATIVE HUMIDITY           | 0-96% non-condensing                          |
| TEMPERATURE RANGE           | 0° to 40°C (32° to 104°F)                     |
| EFFICIENCY AT MAX. LOAD     | 90.3%                                         |
| MAX NUMBER OF BATTERY PACKS | 4                                             |
| OUTPUT FREQUENCY            | 50/60 Hz                                      |
| OUTPUT POWER FACTOR         | 0.9                                           |
| OUTPUT VOLTAGE RANGE        | ±1% steady-state                              |
| RUNTIME AT FULL LOAD        | 6 min                                         |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



**Eaton Corporation plc**

Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.