

Especificaciones

Eaton 9PX1500GRT-L



Eaton 9PX lithium ion UPS, 2U, 1500 VA, 1350 W at 208V, C14 input, Outputs: (8) C13, 208V

La foto es representativa



General specifications

PRODUCT NAME	Eaton 9PX UPS
---------------------	---------------

CATALOG NUMBER	9PX1500GRT-L
-----------------------	--------------

UPC	743172105400
------------	--------------

PRODUCT LENGTH/DEPTH	17.72 in
-----------------------------	----------

PRODUCT HEIGHT	3.41 in
-----------------------	---------

PRODUCT WIDTH	17.32 in
----------------------	----------

PRODUCT WEIGHT	34.83 lb
-----------------------	----------

COMPLIANCES	CE Marked FCC part 15 Class B IEC 62040-2 Cat C1
--------------------	--

CERTIFICATIONS	NOM cTUVus ICC-ES AC156 OSHPD Seismic certified
-----------------------	--



Powering Business Worldwide

Especificaciones del producto

TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	2U
COLOR	Black/silver
VA RATING	1500 VA
WATTAGE	1350 W
RACK MOUNTING KIT	Yes
PACKAGE CONTENTS	• UPS • Quick start guide • Safety instructions • USB communication cable • RS-232 serial communication cable • 4-post rail for 19-inch enclosures • Software leaflet • Software leaflet • 2 pedestals for tower position
INTERNAL BYPASS	Yes
INPUT CONNECTION	C14
INPUT CORD LENGTH	6 ft detachable
INPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240/250V)
INPUT FREQUENCY RANGE	60 Hz: 50-70 Hz, 50 Hz: 40-60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(8) C13, 208V
NUMBER OF OUTPUTS C13	8
OUTPUT WAVEFORM	True sine wave
VOLTAGE	208 V
OUTPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240/250V)
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	Integrated battery management system (BMS) for temperature regulation and life cycle monitoring
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)

Recursos

BATTERY TYPE	Lithium-ion
EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM48RT-L
STANDARD FACTORY WARRANTY	• 5-YEAR FACTORY WARRANTY • - 5 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
BATTERY CHEMISTRY	Lithium Iron Phosphate (LiFePo4)
COMMUNICATION	RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included
EXPANSION SLOTS	• (1) Mini-Slot (MS) expansion port. The following optional connectivity cards may be ordered separately. • Gigabit Network Card part number: NETWORK-M3 • Modbus card part number: INDGW-M2 • Relay card part number: RELAY-MS
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 494, Battery: 731
NOISE LEVEL	<47 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
EFFICIENCY AT MAX. LOAD	92 %
MAX NUMBER OF BATTERY PACKS	4
OUTPUT FREQUENCY	50/60 Hz

OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	12 min

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.

