

Especificaciones

La foto es representativa

Eaton 9PX1500RTN-L

Eaton 9PX lithium ion UPS, 2U, 1500 VA, 1350 W, 5-15P input, Outputs: (8) 5-15R, 120V, includes network card

General specifications

PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX1500RTN-L
UPC	786689526160
PRODUCT LENGTH/DEPTH	17.7 in
PRODUCT HEIGHT	3.4 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	36.5 lb
COMPLIANCES	FCC part 15 Class B CE Marked IEC 62040-2 Cat C1
CERTIFICATIONS	cULus Listed NOM ICC-ES AC156 OSHPD Seismic certified

Especificaciones del producto

Recursos

SPECIAL FEATURES	Gigabit Network Card (NETWORK-M3) included
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	2U
COLOR	Black/silver
VA RATING	1500 VA
WATTAGE	1350 W
RACK MOUNTING KIT	Yes

PACKAGE CONTENTS	• UPS • Quick start guide • Safety instructions • USB communication cable • RS-232 serial communication cable • 4-post rail for 19-inch enclosures • Software leaflet • Software leaflet • 2 pedestals for tower position • Gigabit Network Card (NETWORK-M3)
-------------------------	---

INTERNAL BYPASS	Yes
INPUT CONNECTION	5-15P
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
INPUT FREQUENCY RANGE	60 Hz: 50-70 Hz, 50 Hz: 40-60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(8) 5-15R, 120V
NUMBER OF OUTPUTS 5-15R	8
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120V
OUTPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	Integrated battery management system

	(BMS) for temperature regulation and life cycle monitoring
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Lithium-ion
EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM48RT-L
STANDARD FACTORY WARRANTY	• 5-YEAR FACTORY WARRANTY • - 5 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
BATTERY CHEMISTRY	Lithium Iron Phosphate (LiFePo4)
COMMUNICATION	RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included
EXPANSION SLOTS	(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M3) included
ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 512, Battery: 897
NOISE LEVEL	<47 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
PROTOCOL	SNMP
EFFICIENCY AT MAX. LOAD	90 %
MAX NUMBER OF	4

BATTERY PACKS	
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	11.2 min

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.

