

Especificaciones

Eaton 9PX3000GLRT



Eaton 9PX UPS, 2U, 3000 VA, 3000 W, L6-20P input, Outputs: (2) L6-20R, (1) L6-30R, 208V

La foto es representativa



General specifications

PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX3000GLRT
UPC	743172081315
PRODUCT LENGTH/DEPTH	23.8 in
PRODUCT HEIGHT	3.4 in
PRODUCT WIDTH	17.3 in
PRODUCT WEIGHT	60.4 lb
COMPLIANCES	IEC 62040-2 Class B Cat C2 CISPR22 Class B FCC part 15 Class B VCCI Class B CE Marked
CERTIFICATIONS	cULus Listed ENERGY STAR certified ICC-ES AC156 OSHPD Seismic certified

Especificaciones del producto

TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	2U
COLOR	Black/silver
VA RATING	3000 VA
WATTAGE	3000 W
RACK MOUNTING KIT	Yes
PACKAGE CONTENTS	• 9PX3000GLRT UPS • Input cable • 4-post rail kit • Safety manual • User manual • Tower pedestals • RS-232 serial cable • USB cable • Intelligent Power Software Suite CD
INTERNAL BYPASS	Yes
INPUT CONNECTION	L6-20P
INPUT CORD LENGTH	6 ft detachable
INPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(2) L6-20R, (1) L6-30R
NUMBER OF OUTPUTS L6-20R	2
NUMBER OF OUTPUTS L6-30R	1
OUTPUT WAVEFORM	True sine wave
VOLTAGE	208 V
OUTPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Sealed, lead-acid

Recursos

EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM72RT
STANDARD FACTORY WARRANTY	• 3-YEAR FACTORY WARRANTY • - 3 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
EXTENDED SERVICE PLANS	• ADVANCED DEPOT EXCHANGE • - 5-year depot repair: 9SW5Y-3000UC • - Expedited parts coverage for 5 years • - Parts, electronics and UPS batteries coverage • - Next business day shipping • - Technical support • • 5-YEAR ON-SITE PLAN: WFLN75XX-6009UC • - On-site parts and labor coverage for years 5 • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next-day response • - Next-day shipping • - Technical support
COMMUNICATION	MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot
EXPANSION SLOTS	• (1) Mini-Slot (MS) expansion port.

The following optional connectivity cards may be ordered separately.

- Gigabit Network Card part number: NETWORK-M3
- Modbus card part number: INDGW-M2
- Relay card part number: RELAY-MS

SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 513, Battery: 741
NOISE LEVEL	<47 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
EFFICIENCY AT MAX. LOAD	93%
MAX NUMBER OF BATTERY PACKS	4
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	1
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	6 min

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc

Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.