

Especificaciones

Eaton 9PX3000RTN-L



Eaton 9PX lithium ion UPS, 2U, 3000VA, 2700W, L5-30P input, Outputs: (6) 5-20R, (1) L5-30R, 120V, network card included

La foto es representativa



General specifications

PRODUCT NAME	Eaton 9PX UPS
---------------------	---------------

CATALOG NUMBER	9PX3000RTN-L
-----------------------	--------------

UPC	786689526184
------------	--------------

PRODUCT LENGTH/DEPTH	23.8 in
-----------------------------	---------

PRODUCT HEIGHT	3.4 in
-----------------------	--------

PRODUCT WIDTH	17.3 in
----------------------	---------

PRODUCT WEIGHT	53.7 lb
-----------------------	---------

COMPLIANCES	CE Marked FCC part 15 Class B IEC 62040-2 Cat C1
--------------------	--

CERTIFICATIONS	cULus Listed NOM ICC-ES AC156 OSHPD Seismic certified
-----------------------	--

Especificaciones del producto

Recursos

SPECIAL FEATURES	Gigabit Network Card (NETWORK-M3) included
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	2U
COLOR	Black/silver
VA RATING	3000 VA
WATTAGE	2700 W
RACK MOUNTING KIT	Yes

PACKAGE CONTENTS

- UPS
- Quick start guide
- Safety instructions
- USB communication cable
- RS-232 serial communication cable
- 4-post rail for 19-inch enclosures
- Software leaflet
- Software leaflet
- 2 pedestals for tower position
- Gigabit Network Card (NETWORK-M3)

INTERNAL BYPASS	Yes
INPUT CONNECTION	L5-30P
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
INPUT FREQUENCY RANGE	60 Hz: 50-70 Hz, 50 Hz: 40-60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(6) 5-20R, (1) L5-30R, 120V
NUMBER OF OUTPUTS 5-20R	6
NUMBER OF OUTPUTS L5-30R	1
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120V
OUTPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
RUNTIME GRAPH	\$row.attributeValue.cdata

BATTERY MANAGEMENT	Integrated battery management system (BMS) for temperature regulation and life cycle monitoring
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Lithium-ion
EXTENDED BATTERY CAPABILITY	Add up to 4 extended battery modules (EBM). Part number 9PXEBM72RT-L
STANDARD FACTORY WARRANTY	• 5-YEAR FACTORY WARRANTY • - 5 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
BATTERY CHEMISTRY	Lithium Iron Phosphate (LiFePo4)
COMMUNICATION	RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included
EXPANSION SLOTS	(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M3) included
ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite
USER INTERFACE	Graphical display, 5-button programmable menu
ALTITUDE	0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)
BTU RATING	Online: 844, Battery: 1462
NOISE LEVEL	<47 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
PROTOCOL	SNMP
EFFICIENCY AT MAX. LOAD	91 %

MAX NUMBER OF BATTERY PACKS	4
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	10.2 min

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.

